

PRODUCT DATA

Date: March 2005

Information Sheet No.: B1592-5

AQUAGRIP 326

WATER BASED ADHESIVE

AQUAGRIP 326 is a formulated adhesive based on an aqueous polyvinyl acetate polymer emulsion.

RECOMMENDED USE

AQUAGRIP 326 is a general purpose woodworking adhesive meeting the requirements of BS 4071.

BONDING INSTRUCTIONS

Adhesive to be applied to a clean, dust and grease free surface at a suitable coating weight to induce maximum bond performance. Adhesive which has been stored for prolonged periods should be agitated before use.

CLEANING: Wash all equipment with water before the adhesive dries. Dried adhesive should be soaked for 24 hours.

TYPICAL CHARACTERISTICS

Drying:	Fast
Bond Strength:	High
Viscosity: Brookfield RVT, Spindle 4, Speed 5 rpm.	135 Poise at 20°C
Total Solids Content:	44%

PACKAGING

Please refer to Customer Service Department for current package sizes.

STORAGE

This product should not be allowed to freeze. Store in sealed containers at 5 – 25°C.

SHELF LIFE

12 months from date of manufacture, under the above conditions of storage.

MATERIAL SAFETY DATA

For further information refer to the relevant Health and Safety Data Sheet.