

PRODUCT DATA

Date: July 2006

Code: 466517/20

PRESTIK 6000

PRE-FORMED SEALING STRIP

Prestik 6000 is a butyl rubber-based pre-formed sealing strip.

It is particularly suitable for use in the caravan industry for sealing between plastic and metal components or combinations of these materials.

Features

- Good tack to enable it to bond to a surface
- Adheres to a wide range of materials
- Excellent water resistance
- Available in a range of profiles

Product Characteristics

Colour	White
Chemical Type	Butyl Rubber
Form	Extruded strip
Solids content	100%
Density	1.6g/cm ³
Packaging / sizes	Various profiles available
Shelf life/storage	At least 12 months from date of manufacture when stored in the original unopened containers in dry conditions within the temperature range +5°C to +25°C

Typical Performance Data (approx.)

Temperature resistance	-18°C to +70°C
Water resistance	Excellent
Sunlight and UV resistance	Good
Detergent solution resistance	Good
Oil and solvent resistance	Not good in general

Directions for use

IMPORTANT

Before embarking on any work involving Prestik 6000, the separate Safety Data Sheet should be carefully studied by those carrying out the work.

Application

Ensure surfaces to be sealed are clean, dry and free from grease or oil. Unreel the required amount of Prestik 6000 attached to its backing paper. Position the tape onto one of the surfaces to be joined and press down to remove any trapped air and ensure good contact is achieved to the surface. Peel off the backing paper by pulling along the length of the strip, not directly away from it. Mate the other surface to the strip and make sure the joint is held under compression by use of appropriate mechanical fixings.

Precautions in Use

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate health and safety data sheet for Prestik 6000.

This Product Data Sheet covers just one of a large range of products supplied by Bostik Limited. Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This Product Data Sheet supersedes all previous technical information on this product, and users of it are cautioned to ensure that it is the current issue. Destroy all previous Product Data Sheets, and if any doubt, contact Bostik Limited, quoting the code number in the top right hand corner on the front of this document. This leaflet is for general guidance only and may contain inappropriate information under particular conditions of use. The company cannot accept any responsibility for loss or damage that may result from the use of this information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm the suitability of this product by their own tests.

Bostik Limited, Common Road, Stafford, ST16 3EH, England

Tel: +44 (0)1785 272727

Fax: +44 (0)1785 257898

www.bostik.co.uk